

RBD340-1

1+1 Redundant, High Grade, C-Band, Non-Inverting, Block DownConverter System.









The **RBD340-1** 1+1 Redundant, Non-Inverting C-Band Block DownConverter system comprises two **IBD340** Block DownConverters, plus an **RCU100** control unit along with matched SHF, L-Band and a complete control interface cable set. It includes all that is required to implement a single feed 1+1 redundant C-Band BDC system, maintaining maximum availability whilst allowing routine maintenance and repair work to be carried out on the standby converter without the normally associated down-time.


The **RBD340-1** system maintains a converter on-line whilst the other is held in hot standby, allowing the user to select the on-line converter. The redundancy unit can be controlled from the front panel (Local mode) or by the RS232/RS485 link to a host computer (Remote mode). In remote mode, the on-line converter can be selected and monitored whilst keeping switch-over automatic in case of failure.

In AUTO mode, the **RCU100** control unit monitors the converter alarm signals via the interface connecting cables and if a fault condition develops within the on-line converter, the **RCU100** automatically switches traffic to the standby unit.

All units are mains powered and are constructed of high grade components to give the ultimate stability, ripple and phase noise performance

Peak Features

-  High stability, Low ripple and excellent phase noise
-  10MHz External Reference option fitted as standard with automatic internal reference back-up
-  Dual mains input & redundant power supplies on control unit fitted as standard
-  Keys removable for security in any position
-  Dual switching arrangement (L-band and SHF)
-  Matched SHF, L-band and converter control interface cable set provided as standard



RBD340-1 Specification

SHF Input

Frequency	3.40-4.20GHz
Connector	50Ω, SMA
Return loss	>18dB

L-Band Output

Frequency	950 to 1750MHz
Connectors	50Ω, SMA (option 3; 75Ω, BNC)
Return loss	>15dB
1dB GCP	+7dBm

System Transfer Characteristics

Conversion gain	17dB ±0.5dB at band centre
Gain stability	±0.5dB from 0 to 40°C
Gain flatness	±1dB full band
	±0.5dB across 40MHz in band.
1+1 changeover	1dB max variation (unit to unit)

RF Performance

LO Phase noise	-75dBc/Hz at 100Hz -92dBc/Hz at 1kHz -100dBc/Hz at 10kHz -107dBc/Hz at 100kHz -125dBc/Hz at 1MHz
Harmonics	Better than -50dBc
Spurious	<-80dBm (in band non-carrier related) <-75dBc (in band carrier related)
3rd Order Intercept	>+18 dBm (standard unit)
LO leakage	-80 dBm (always out of band)

L-Band Monitor (Option 2) on converters

Connection	Option 2a; 50Ω SMA on rear panel
Connection	Option 2b; 50Ω SMA on front panel
Level	-20dBc ±3dB

Internal Reference Stability

Stability	<1 x 10 ⁻¹⁰ per second
Temp. Stability	<±5 x 10 ⁻⁸ (0 to +50°C)
Ageing	<±5 x 10 ⁻⁹ per day

High stability - Option 8

Stability	<2 x 10 ⁻¹² over 1s, <2 x 10 ⁻¹⁰ per day
Ageing	<2 x 10 ⁻⁸ per year
Temp. stability	<2 x 10 ⁻⁹ over 0 to 50°C

External Reference Input

Frequency	10MHz (5MHz selectable)
Connector	50Ω, BNC
Level	0dBm ±3dB
Required phase noise	Better than 50dBc/Hz of output Phase Noise

Switch Element Parameters

Switching speed	<15ms
Type	Co-axial, latching
Response speed	<150ms (from fault to switch completion)

Mechanical

Width	19" standard rack mount
System Height	3U (1U (1.75") x 3)
Depth	~400mm (15.7"), plus connectors
Construction	Aluminium chassis
Weight	13kgs (~28lbs) approx.

Environmental

Operating temp.	0°C to +50°C
EMC	EN 55022 part B & EN 50082-1
Safety	EN 60950

Power Supply

Voltage	115/230VAC±10%, selectable, Dual PSU on RCU
Frequency	50/60Hz
System Power	100Watts max.

Control System


Rem/Loc switch	2 position key switch, selects remote or local mode.
Auto/A/B switch	3 position key switch, selects converter A or B to traffic manually, or automatically.
Remote control	RS232/RS485 port (Option 9; Ethernet replaces RS232/485 port)
Converter alarm	PSU fail, LO lock fail & Amp fail

Options

- 2a) -20dBc L band monitor on rear panel (SMA).
- 2b) -20dBc L band monitor on front panel (SMA).
- 3) 75Ω interface at L band.
- 8) High Stability Internal reference option.
- 9) Ethernet interface, replaces RS232/485 port.

Note: Some of the above options have an impact on the general performance specification, factory guidance should be sought if this is thought to be critical.

Rear panel Views



Peak Communications reserves the right to alter the specifications of this equipment without prior notice. RBD340-1-291208.

Peak Communications Ltd, 22 West Park Street, Brighouse, HD6 1DU, England

Tel; +44 (0)1484 714200 Sales; +44 (0)1484 714229 Fax; +44 (0)1484 723666 Email; sales@peakcom.co.uk Web; www.peakcom.co.uk